

High-speed stubble rake（Suspension-type）							
NO	Item	unit	2m	2.5m	3.5m	4m	5.5m
1	Machine weight	kg	1250	1450	1740	1990	2735
2	Machine size (L ×W ×H)	mm	2530×2000×1540	2530×2500×1540	2530×3500×1540	2530×4000×1540	2530×5500×1540
3	Main beam dimension	mm	100×100				
4	Disc diameter	mm	620	620	620	620	620
5	Crusher roll diameter	mm	350	350	350	350	350
6	Number of discs	pcs	14	16	24	28	38
7	Working width	mm	2000	2500	3500	4000	5500
8	Supporting power	hp	90-120	100-140	≥160	≥180	4480
High-speed stubble rake(Towed-type)							
NO	Item	Unit	4m	5m	6m	7m	7.5m
1	Machine weight	kg	4480	5600	6720	7840	8400
2	Machine size (L×W ×H)	mm	7300×4550×1900	7300×5500×1900	7300×6550×1900	7300×7550×1900	7300×8050×1900
3	Disc diameter	mm	620				
4	Crusher roll diameter	mm	400	400	400	400	400
5	Number of discs	pcs	32	40	48	56	60
6	Working width	mm	4000	5000	6000	7000	7500
7	Supporting power	hp	180-220	200-240	220-260	260-300	≥300
8	Tyre type	/	16/70-20				